

COMPARISON WITH OTHER PANELS

- ▶ rainproof and shock resistant aluminum body
- ▶ 100% silent fan-free operation
- ▶ 3 times more light output
- ▶ much longer through (750 Lux at 6 meters)
- ▶ more than bi-colour 2700K to 6500K
- ▶ digital display with shock resistant buttons
- ▶ perfect color rendition & consistency lamp to lamp
- ▶ professional DMX RDM with XLR-5 connector
- ▶ wide power input 12-35 VDC / 90-264 VAC
- ▶ affordable European quality
- ▶ 2 years warranty 100% made & designed in Barcelona (Spain)



www.thelight.com.es

info@thelight.com.es

Intellectual Property

THELIGHT VELVET light technology is protected under spanish patents and international patents pending

2014 © Copyright THELIGHT. All rights reserved.

the beaming rainproof 1x1 LED panel



RAINPROOF

Rocky body 100% aluminum

SILENT

Fan-free operation

POWERFUL

2700 Lux at 3m / 10 ft



The unique aLL-in-one Light



LONG THROW BEAM

Incredibly powerful 15° or 30° beam of light to be used up to 15 meters distance
The light can be easily shaped and soften with the choice of magnetic attach diffusers

MORE THAN BI-COLOR

VELVET Power 1 is more than tungsten & daylight in the same unit: you can adjust color temperature from 2700K to 6500K

AC/DC POWERED

VELVET is always ready to operate worldwide: using any battery from 12 to 35 VDC with **Vlock or Gold battery mount** with universal **AC power 90-264 VAC**

VELVET QUALITY WHITE LIGHT

CRI >90 to get perfect skin tones and real colors with any HD or photo camera
Professional and consistent color rendition
Absolutely consistent lamp to lamp to mix with any VELVET panel and get the same high quality and color reproduction

QUICK SETUP

On-board control, digital display and **shock resistant buttons** color temperature **instantly adjustable** from 2700K to 6500K dimmer smooth and flicker-free 0 to 100 with no color shift

ADVANCED DMX RDM

bi-directional DMX remote control even without a controller!
Master-slave function: to operate without console

THELIGHT introduces **Rainproof VELVET Power 1** the most robust and advanced LED panel producing long throw light without noisy fans

MADE TO LAST

Rainproof IP54

Robust 100% aluminum body made to endure the tougher working conditions on any location or studio

Silent operation

THELIGHT state of the art passive cooling technology keep LED in their optimum temperature to last beyond 50.000 hours without fans to be serviced

ADVANTAGES

- ▶ Rainproof and shock resistant aluminum body
- ▶ More than bi-colour 2700K to 6500K
- ▶ Maintenance free without fans
- ▶ Long throw beam light
- ▶ High output 900 Lux at 10 meters
- ▶ Worldwide AC & DC powered
- ▶ On-board and DMX control
- ▶ Thin and portable
- ▶ Modular design for multipanel
- ▶ Flicker free up to 3000 fps
- ▶ Silent fan-free operation
- ▶ 100% Made in Barcelona (Spain)



VELVET Power 1 includes:

- ▶ 100% aluminum IP54 rainproof LED panel
- ▶ On-board and DMX digital control over:
 - ▶ Color temperature from 2700K to 6500K
 - ▶ smooth Flicker-free dimming 0 to 100
- ▶ XLR-3 input for battery power 12-35VDC
- ▶ XLR-5 input connector for remote DMX control
- ▶ adjustable yoke with combined 28 / 16mm pin
- ▶ two years warranty

TECHNICAL SPECIFICATIONS

VELVET Power 1 Flood

VELVET Power 1 Spot

COLOR TEMPERATURE	digitally adjustable from 2700K to 6500K	
LIGHT INTENSITY	dimnable 0 to 100 (smooth and flicker-free)	
DIMENSIONS	385 x 308 x 68 mm	
WEIGHT	4,5 Kg	
POWER DRAW	100W (7 Amps at 14,4 VDC - 0,44 Amps at 230VAC)	
POWER SUPPLY	12-35V DC via XLR-3 14,4V DC Vlock or Gold mount battery plate 90-264V AC 50/60Hz	
PHOTOMETRICS	20.000 Lux / 1.850 fc at 1m / 3 feet 2.700 Lux / 250 fc at 3m / 10 feet 750 Lux / 71 fc at 6m / 20 feet	42.000 Lux / 3.890 fc at 1m / 3 feet 8.500 Lux / 787 fc at 3m / 10 feet 1.800 Lux / 167 fc at 6m / 20 feet
BEAM ANGLE	30° tunable with optic diffusers	15°
LED RATED LIFE	more than 50.000 hours	
COOLING	no noise, fan-free passive cooling	
PROTECTION & CONSTRUCTION	rainproof IP54 rated, made of black anodized extruded aluminum and black powder coated sheet aluminum	
VELVET LED TECHNOLOGY	selected BIN High-power LED + THELIGHT custom optics + CPU software control	
QUICK MOUNTING ACCESSORIES	AC power supply, Vlock or Gold adapter, magnetic attach diffusers, pole-op yoke, multipanel yokes, removable barn doors, DMX splitter cable, hard case, Cordura soft case	



Specifications subjects to change without notice