

f=14mm V-DSLR ED AS IF UMC II (for Cinema)

SPECIFICATIONS		1:3.1 14mm ED AS IF UMC II									
APERTURE RANGE(T-STOP)		T3.1 to T22									
OPTICAL CONSTRUCTION		14 ELEMENTS IN 10 GROUPS (1 GLASS ASP & 1 HYBRID ASP)									
MINIMUM FOCUSING DISTANCE		0.28m(0.92ft)									
FILTER SIZE		NONE									
MAXIMUM DIAMETER		Φ87mm									
MOUNT		NIKON	CANON EOS	PENTAX K	SONY α	CANON M	FUJIFILM X	SAMSUNG NX	SONY E	FOUR-THIRDS	MICRO FOUR-THIRDS
ANGLE OF VIEW	35mm	115.7°	115.7°	115.7°	115.7°	-	-	-	115.7°	-	-
	APS-C	93.9°	89.9°	93.9°	93.9°	89.9°	93.9°	93.9°	93.9°	-	-
	FOUR-THIRDS (4/3")	-	-	-	-	-	-	-	-	76.24°	76.24°
LENGTH(LENS MOUNT TO FRONT)		93.6mm	96.1mm	94.6mm	95.6mm	122mm	122.4mm	114.6mm	122.1mm	101.4mm	120.9mm
WEIGHT		605g	620g	595g	615g	690g	695g	640g	640g	640g	650g
GEAR	MODULE	0.8									
	A	5.3mm									
	B	4mm									
	C	42.1mm									
	D	8mm	10.5mm	9mm	10mm	36.4mm	36.8mm	29mm	36.5mm	15.8mm	35.3mm
	FOCUS DIAMETER	Φ81.6mm									
	APERTURE DIAMETER	Φ70.4mm	Φ73.6mm								

Drawing

