

f=35mm V-DSLR AS UMC II

(for Cinema)

SPECIFICATIONS		1:1.5 35mm AS UMC II									
APERTURE RANGE(T-STOP)		T1.5 to T22									
OPTICAL CONSTRUCTION		12 ELEMENTS IN 10 GROUPS (1 ASPHERICAL LENS)									
MINIMUM FOCUSING DISTANCE		0.3m(0.98ft)									
FILTER SIZE		Φ77.0mm									
MAXIMUM DIAMETER		Φ83.0mm									
MOUNT		NIKON	CANON EOS	PENTAX K	SONY α	CANON M	FUJIFILM X	SAMSUNG NX	SONY E	FOUR-THIRDS	MICRO FOUR-THIRDS
ANGLE OF VIEW	35mm	63.1°	63.1°	63.1°	63.1°	-	-	-	63.1°	-	-
	APS-C	43.2°	40.8°	43.2°	43.2°	40.8°	43.2°	43.2°	43.2°	-	-
	FOUR-THIRDS 4/3"	-	-	-	-	-	-	-	-	33.4°	33.4°
LENGTH(LENS MOUNT TO FRONT)		109mm	111.5mm	110mm	111mm	137.4mm	137.8mm	130mm	137.5mm	116.8mm	136.3mm
WEIGHT(CAP,HOOD DETACHABLE)		685g	700g	670g	695g	730g	775g	720g	720g	720g	770g
GEAR	MODULE	0.8									
	A	7mm									
	B	4mm									
	C	43.8mm									
	D	8mm	10.5mm	9mm	10mm	36.4mm	36.8mm	29mm	36.5mm	15.8mm	35.3mm
	FOCUS DIAMETER	Φ81.6mm									
APERTURE DIAMETER		Φ70.4mm	Φ73.6mm								

Drawing

