

# Intensity Pro 4K



Intensity Pro 4K lets you capture and playback on PCIe Mac, Windows and Linux computers. Featuring HDMI and analog breakout connections, Intensity Pro 4K works with NTSC/PAL, HD and Ultra HD video with or without compression and is compatible with all popular video editing, audio, and streaming software. DaVinci Resolve Lite and Media Express software are included free so you get professional editing, grading and media management without having to buy extra software!

\$199

## Connections

### HDMI Video Input

1 x HDMI type A connector.

### HDMI Video Output

1 x HDMI type A connector.

### HDMI Audio Input

8 Channels embedded in SD, HD and Ultra HD.

### HDMI Audio Output

8 Channels embedded in SD, HD and Ultra HD.

### Analog Video Input

Component, Composite or S-Video.

### Analog Video Output

Component, Composite or S-Video.

### Analog Audio Input

2 Channel RCA HiFi audio in 24-bit.

### Analog Audio Output

2 Channel RCA HiFi audio in 24-bit.

### SPDIF Audio Output


2 Channel 24-bit.

### Multiple Rate Support

HDMI video connections are switchable between SD, HD and Ultra HD. Component analog video connections are switchable between SD and HD.

### Computer Interface

PCI Express 4 lane, compatible with 4, 8 and 16 lane PCIe slots.



---

## Standards

### SD Format Support

625i50 PAL, 525i59.94 NTSC, 625p50 PAL, 525p59.94 NTSC

### HD Format Support

720p50, 720p59.94, 720p60  
1080p23.98, 1080p24, 1080p25,  
1080p29.97, 1080p30, 1080p50,  
1080p59.94, 1080p60  
1080i50, 1080i59.94, 1080i60

### Ultra HD Format Support

2160p23.98, 2160p24, 2160p25,  
2160p29.97, 2160p30

### HDMI Video Sampling

RGB 4:4:4 in HD and YUV 4:2:2 in Ultra HD.

### HDMI Audio Sampling

Television standard sample rate of 48kHz and 24-bit.

### Color Space

REC 601, REC 709.

### HDMI Color Precision

10-bit

### HDMI Configuration

HDMI 1.4b supports Deep Color and automatically configures to connected display.

### Copy Protection

HDMI input is unable to capture from copy protected HDMI sources. Always confirm copyright ownership before capture or distribution of content.

---

## Processing

### UHD/HD Down Conversion

Software based down conversion during video playback.

### HD Up Conversion

Real time SD to 1080HD and 720HD during video capture.

### Real Time Effects

Final Cut Pro X internal effects.  
Premiere Pro CC Mercury Playback Engine effects. Avid Media Composer internal effects.

---

## Software

### Software Included

DaVinci Resolve, Media Express, Disk Speed Test, LiveKey, Blackmagic Desktop Video Utility and Blackmagic driver on Mac OS X and Windows. Blackmagic Desktop Video Utility and Blackmagic driver on Linux.

### Internal Software Upgrade

Firmware built into software driver. Loaded at system start or via updater software.

---

## Operating Systems



Mac OS X 10.10 Yosemite,  
Mac OS X 10.11 El Capitan  
or later.




Windows 7, 8.1 and 10,  
all 64-bit.



Linux

---

## Physical Specifications



0.22 lb

---

## Physical Installation

PCI Express 4 lane, compatible with 4, 8, 16 lane PCI Express slots on Mac OS X, Windows 7 and 8, and Linux. Please check the Support pages to see the full system requirements.

---

## Environmental Specifications

### Operating Temperature

5° to 40° C (32° to 104° F)

### Storage Temperature

-20° to 45° C (-4° to 113° F)

### Relative Humidity

0% to 90% non-condensing

---

## What's Included

Intensity Pro 4K  
Software SD card.  
Breakout Cable

---

## Warranty

12 Months Limited Warranty.

---

All items on this website are copyright Blackmagic Design Pty. Ltd. 2017, all rights reserved.  
All trademarks are property of their respective owners. MSRP excludes sales taxes/duties and shipping costs.

Blackmagic Design Authorized Reseller