

# Smart Videohub CleanSwitch 12x12



Compact 6G-SDI router with built in re-synchronizers on all inputs allows clean switching between all video sources of the same video standard, and can be used as 12 re-synchronizers for automatic re-timing of SDI feeds. Smart Videohub CleanSwitch supports 12 inputs and 12 outputs in virtually all SD, HD and Ultra HD video formats. Supports multiple formats on the same router at the same time and will clean switch between multiple formats that match the reference frame rate when the switching is between the same video standard. Includes front panel button and spin knob routing, elegant machined metal front panel with LCD for routing display and video monitoring and remote Ethernet control.


\$1,495

## Connections

<b>SDI Video Input</b> 12
<b>SDI Video Output</b> 12
<b>SDI Rates</b> 270Mb, 1.5G, 3G, 6G.
<b>Video Input Re-Sync</b> On all 12 inputs for clean switch.
<b>SDI Relocking</b> On all SDI outputs.
<b>Reference Input</b> Tri-Sync or Black Burst.

<b>Control Panel Connection</b> Ethernet.
<b>Serial Control Connection</b> RJ-6 RS RS-422.
<b>Multi Rate Support</b> Auto detection of SD, HD or 6G-SDI. Simultaneous routing of 4K, HD and SD video.
<b>Updates</b> USB.

<b>Front Panel Router Control</b> 12 buttons for local control of Videohub. 6 buttons and scroll wheel for control of LCD display or RJ45 Ethernet.
<b>Router Configuration</b> Via front panel LCD or RJ45 Ethernet.
<b>RS-422 Router Control</b> 1 x input for controlling router crosspoint switching.



## Standards

### SD Format Support

525i59.94 NTSC, 625i50 PAL.

### HD Format Support

720p50, 720p59.94, 720p60  
1080p23.98, 1080p24, 1080p25,  
1080p29.97, 1080p30, 1080p50,  
1080p59.94, 1080p60  
1080PsF23.98, 1080PsF24, 1080PsF25,  
1080PsF9.97, 1080PsF30  
1080i50, 1080i59.94, 1080i60

### 2K Format Support

2K DCI 23.98p, 2K DCI 24p, 2K DCI 25p  
2K DCI23.98PsF, 2K DCI 24PsF,  
2K DCI 25PsF

### Ultra HD Format Support

2160p23.98, 2160p24, 2160p25,  
2160p29.97, 2160p30

### 4K Format Support

4K DCI 23.98p, 4K DCI 24p, 4K DCI  
25p, 4K DCI 29.97p, 4K DCI 30p

### SDI Compliance

SMPTE 259M, SMPTE 292M,  
SMPTE 296M, SMPTE 310M,  
SMPTE 425M Level B, ITU-R BT.656  
and ITU-R BT.601.

### SDI Video rates

SDI video inputs are switchable  
between standard definition, high  
definition and 4K. SDI switches  
between 270 Mb/s standard definition  
SDI, 1.5 Gb/s HD-SDI, 3G-SDI and 6G-  
SDI.

### SDI Video Sampling

4:2:2 and 4:4:4

### SDI Audio Sampling

Television standard sample rate of  
48kHz and 24 bit.

### SDI Color Precision

4:2:2 and 4:4:4 10 bit.

### SDI Color Space

YUV or RGB.

### SDI Auto Switching

Automatically selects between SD-SDI,  
HD-SDI, and 6G-SDI on each input.

### SDI Metadata Support

Video payload identification ancillary  
data as per SMPTE 352M.

## Control

### Built-in Control Panel

12 buttons for local control of Videohub  
with 6 buttons and scroll wheel for menu  
control. 2.2 inch color display.

### External Control Panel

Includes Blackmagic Videohub  
software control panel for Mac OS X  
and Windows. Supports Blackmagic  
Smart Control and Blackmagic Master  
Control hardware panels. Includes  
Blackmagic Videohub SDK and  
Ethernet Videohub Control Protocol.

---

## Software

### Software Control

Router control included free for Windows™ and Mac OS X™.

### Internal Software Upgrade

Via included updater application.

---

## Operating Systems



Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan or later.



Windows 8.1 or Windows 10.

---

## Display

Built-in LCD for video and menu settings.

---

## Power Requirements

### Power Fail Protection

Router connections preserved and restored instantly at power on.

### Power Supply

IEC power cable required. 90 - 240V AC input.

---

## Physical Specifications



## Physical Installation

1 rack unit size. Less than 6 inches deep.

---

## Environmental Specifications

### Operating Temperature

0° to 40° C (32° to 104° F)

### Storage Temperature

-20° to 45° C (-4° to 113° F)

### Relative Humidity

0% to 90% non-condensing

---

## What's Included

Smart Videohub CleanSwitch 12x12  
SD card with software and manual

---

---

# Warranty

12 Month Limited Manufacturer's Warranty.

---

All items on this website are copyright Blackmagic Design Pty. Ltd. 2017, all rights reserved.  
All trademarks are property of their respective owners. MSRP excludes sales taxes/duties and shipping costs.

Blackmagic Design Authorized Reseller