

Model Name	PTC-140T
Product Name	HDBaseT PTZ Camera
Video format	1080p 60/59.94/50/30/29.97/25 1080i 60/59.94/50 720p 60/50/30/25/59.94/29.97
Image Sensor	1/2.8 inch high quality HD CMOS sensor
Effective Pixels (approx.)	2.07 Mega pixels
S/N Ratio	>55dB
Min. Illumination	0.5Lux (F1.8, AGC ON)
Electronic Shutter	Auto/ Manual
Zoom Ratio	20x Optical Zoom, 10x Digital Zoom
Gamma Control	Off/ Normal
Iris Control	Auto/ Manual
Digital Noise Reductions	Yes
On-Screen Display (OSD)	English, Simplified Chinese
White Balance	Auto / Manual/ One Push/ 3000K/ 4000K/5000K/6500K
AGC / Gain Control	Auto/ Manual
Mirror / Flip Image	Yes
Focus Mode	Auto / Manual
Panning/Tilting Range	Pan: 340° , Tilt: +90° to -30°
Panning/Tilting Speed	Pan: 0.1~60°/sec Tilt: 0.1~30°/sec
Preset	255 Position
Focal Length	f= 5.2 (wide) ~98 (tele) mm F1.6 to F3.5
Field of View (Horizontal, Wide)	Approx. 54.7° (WIDE END) / 3.3° (TELE END)
Image Compensation	Backlight Compensation
Video Output	HDBaseT (PoE) x1 RJ-45 x1
Audio Input	Line In (IP Stream Output)

<b>Tally LED</b>	Dual color (Red, Green)
<b>Filter</b>	M52.0 x 0.75 Thread with UV Protection
<b>Protocol</b>	VISCA, DVIP
<b>Remote Control Interface and Transmit Distance</b>	RS-232 Lan (RJ-45)
<b>F/W Update</b>	Ethernet
<b>IR Control</b>	Yes
<b>Camera Control Unit</b>	RMC-300
<b>Size of Screw Hole for Tripod</b>	1/4-20 UNC
<b>Accessories</b>	WM-1
<b>Color</b>	Dark Blue/ White