

Specification

Spec.	RL21 – 75	RL31 – 100	RL31 – 150
Light Output	1500lux @1m; 2700K 1720lux @1m; 6500K	2000lux @1m; 2700K 2300lux @1m; 6500K	3100lux @1m; 2700K 3500lux @1m; 6500K
Power Consumption	75W	100W	150W
CRI / TLCI	CRI 96 ~ 98 / TLCI 98	CRI 96 ~ 98 / TLCI 98	CRI 96 ~ 98 / TLCI 98
Color Temperature	2700K ~ 6500K	2700K ~ 6500K	2700K ~ 6500K
Dimmer	0 ~ 100% DIM / DMX 512 / Manual	0 ~ 100% DIM / DMX 512 / Manual	0 ~ 100% DIM / DMX 512 / Manual
Color Temp. Control	100K Step	100K Step	100K Step
Light Output Connector	6Pin x 1	6Pin x 1	6Pin x 1
IP Rating	IP64	IP64	IP64
Input	12 ~ 24V DC(4Pin)	12 ~ 24V DC(4Pin)	12 ~ 24V DC(4Pin)
DMX In / Out	5Pin XLR	5Pin XLR	5Pin XLR
Beam Angle	120°	120°	120°
LEDs	312	432	684
Battery Mounts	V-Mount / Gold Mount	V-Mount / Gold Mount	V-Mount / Gold Mount
Mat Dimensions (ft)	2' x 1'	3' x 1'	3' x 1'
Mat Weight	440g	700g	720g

Spec.	RL33 – 200	RL33 – 300	RL66 – 1200
Light Output	4000lux @1m; 2700K 4600lux @1m; 6500K	6200lux @1m; 2700K 7000lux @1m; 6500K	24800lux @1m; 2700K 28000lux @1m; 6500K
Power Consumption	200W	300W	1200W
CRI / TLCI	CRI 96 ~ 98 / TLCI 98	CRI 96 ~ 98 / TLCI 98	CRI 96 ~ 98 / TLCI 98
Color Temperature	2700K ~ 6500K	2700K ~ 6500K	2700K ~ 6500K
Dimmer	0 ~ 100% DIM / DMX 512 / Manual	0 ~ 100% DIM / DMX 512 / Manual	0 ~ 100% DIM / DMX 512 / Manual
Color Temp. Control	100K Step	100K Step	100K Step
Light Output Connector	9Pin x 1, 6Pin x 2	9Pin x 1, 6Pin x 2	18Pin x 1, 9Pin x 4
IP Rating	IP64	IP64	IP64
Input	80 ~ 260V AC, 50~60HZ / 24V DC	80 ~ 260V AC, 50~60HZ / 24V DC	80 ~ 260V AC, 50~60HZ / 48V DC
DMX In / Out	5Pin XLR	5Pin XLR	5Pin XLR
Beam Angle	120°	120°	120°
LEDs	864	1368	5472
Battery Mounts	-	-	-
Mat Dimensions (ft)	3' x 3'	3' x 3'	6' x 6'
Mat Weight	1400g	1440g	5760g



A Whole New Level of Experience

Fomex RollLite is an LED lighting system that gives you a whole new level of experience that you have never felt before.

Fomex RollLite precisely emphasizes the subject's true color with a high light intensity, and is lightweight, and easy to move and install, perfectly meets the demanding requirements of professional lighting.



SCAN
QR CODE
TO SEE FOMEX

Unit701, 31-18Gil, Seongsui-ro, Seongdong-gu, Seoul 04787 Korea Tel +82 2 545 0004 Fax +82 2 3444 9399
www.fomex.com e-mail : info@fomex.com
All product specifications are subject to change without notice

VER. 201902

FOMEX RollLite

Perfect and Delicate Color

Fomex RollLite is precise LED lighting to express color that is perfect under any circumstances.

Fomex RollLite maximizes color flexibility, allowing you to choose a color temperatures from 2700K to 6500K and ensures TLCI98 and CRI96 to achieve the most exact color with your intent to look at the subject.




Separately and Together, Easy and Various Installation

Fomex RollLite is an innovative LED lighting system that can be transformed freely depending on the location and circumstances. Mats can be combined to expand to the desired size as needed. Fomex RollLite uses an integral snap-grommet to allow quick and easy installation on the Butterfly, X-mounts for stand, and ceilings or more.



When using RollLite outside, it meets IP64



Connector

Can be set horizontal or vertically (90deg) and can be then fixed in position



X-Mount for RL21, RL31, RL33

All new X-Mount made by die casting